

OFFICE GUILLOTINE EBA 485 A

With automatic clamp

STANDARD FEATURES

- 475 mm cutting length
- electro-mechanical blade and clamp drive
- optical cutting line indicator with bright and durable LEDs
- spindle guided backgauge with hand crank
- digital measurement readout for backgauge positioning (cm or inches)
- adjustable backgauge with narrow separations and plastic gliders
- two side lays each on front and rear tables
- blade from high quality steel
- solid steel blade carrier and adjustable blade guides automatic clamping system, guided on both sides for evenly distributed clamping
- pressure (clamp can be lowered or raised independently from blade)
- solid all-metal construction
- complete with stand and storage shelf

SAFETY FEATURES

"SCS" (SAFETY CUTTING SYSTEM)

- hinged, electronically controlled safety guard on the front table
- transparent safety cover on the rear table
- main switch and safety lock with key
- electronically controlled true two-hand operation
- 24 volt controls (low voltage)
- patented safety drive
- automatic blade and clamp return from every position
- disc brake for instant blade stop
- blade changing device with covered cutting edge
- blade depth adjustment from the outside of the machine
- easy blade change from the front of the machine without removing covers



TECHNICAL DATA	EBA 485 A
Cutting length in mm	475
Cutting height in mm	80
Insertion depth in mm	458
Front table depth in mm	340
Minimum cut in mm	30
Power connection in volts/Hz (other voltages available)	230 / 50
Motor capacity in kW	1.42
Dimensions W x D x H in mm	755 x 970 x 1230
Weight in kgs	209

The technical data is approximate. Subject to change. 10/10

