

EBA

first class security

OFFICE DOCUMENT AND EDP SHREDDERS

EBA 5141 S / EBA 5141 C

EBA 5141 CC / EBA 5141 CCC

INNOVATIVE HIGH CAPACITY OFFICE SHREDDERS –
HIGH PERFORMANCE AND LARGE VOLUME

- "SPS"- (Safety Protection System) package:
 - electronically controlled, transparent safety flap in the feed opening as additional safety element
 - automatic reverse and power cut-off in case of paper jam with automatic cut-off
 - automatic stop if the shred bag is full
 - electronic door protection via a magnetic proximity switch
 - double motor protection
 - energy-saving mode after 1 hour
- modern keypad with start/stop/reverse buttons and optical indicators for the operational status of the shredder
- powerful 1600 watt motor for continuous operation
- large feed opening of 405 mm for convenient feeding of large paper formats
- automatic start and stop via a photo cell
- "ECC - Electronic Capacity Control" – indication of the used sheet capacity during shredding process
- automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance
- high-quality wooden cabinet, mobile on castors
- especially high volume for the shreds (225 litres)
- plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag
- dust-proof gear box housing
- sturdy steel cutting mechanism that swallows paper clips (exception: models EBA 5141 CC and EBA 5141 CCC)
- 5 years guarantee on the solid steel cutting shafts*
- suitable for safe shredding of CDs or DVDs (EBA 5141 S and EBA 5141 C)
- attractive colour combination: silver / dark grey
- quality "Made in Germany"



| TECHNICAL DATA | EBA 5141 S | EBA 5141 C | | EBA 5141 CC | EBA 5141 CCC |
|--|------------------|------------------|------------------|------------------|------------------|
| Insertion width in mm | 405 | 405 | 405 | 405 | 405 |
| Cutting width in mm | 6 | 4 x 40 | 2 x 15 | 0.8 x 12 | 0.8 x 5 |
| Sheet capacity A4 sheets, 70 g/m ² 80 g/m ² | 50-55 42-47 | 40-45 34-39 | 25-30 21-26 | 17-19 14-16 | 10-11 8-9 |
| DIN security level | 2 | 3 | 4 | 5 | Level 6 |
| Motor capacity in watts | 1600 | 1600 | 1600 | 1600 | 1600 |
| Power connection in volts/Hz** | 230/50 | 230/50 | 230/50 | 230/50 | 230/50 |
| Dimensions W x D x H in mm | 640 x 590 x 1010 | 640 x 590 x 1010 | 640 x 590 x 1010 | 640 x 590 x 1010 | 640 x 590 x 1010 |
| Bag volume in litres | 225 | 225 | 225 | 225 | 225 |
| Weight in kgs | 115 | 115 | 115 | 115 | 115 |

The technical data is approximate. Subject to change. 01/2007

* except fine cut version "CC" and "CCC" – guarantee 1 year

** other voltages available

OFFICE DOCUMENT AND EDP SHREDDERS EBA 5141 + ACCESSORIES

| MODEL | ARTICLE NO. | EAN-CODE |
|--|-------------|---------------|
| EBA 5141 S, 6 mm 230 V, 50 Hz* | 51416111 | 4018351114068 |
| EBA 5141 C, 4 x 40 mm 230 V, 50 Hz* | 51419111 | 4018351114143 |
| EBA 5141 C, 2 x 15 mm 230 V, 50 Hz* | 51411111 | 4018351114242 |
| EBA 5141 CC, 0.8 x 12 mm 230 V, 50 Hz* | 51418111 | 4018351114365 |
| EBA 5141 CCC, 0.8 x 5 mm 230 V, 50 Hz* | 51417111 | 4018351114372 |
| Plastic bags for EBA 5141 (50 pieces per packing unit) | 9000410 | 4019364940705 |
| Shredder oil for EBA 5141 (5 x 1 litre per packing unit) | 9000620 | 4019364950858 |

* other voltages available

TRANSPARENT SAFETY FLAP



The safety flap in the feed opening is an additional safety element to keep fingers, ties or other objects away from the cutting shafts.

KEYPAD



Modern keypad with start/stop/reverse buttons and optical indicators for the operational status of the shredder.

"ECC" CONTROL



"ECC" – Electronic Capacity Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

AUTOMATIC OIL INJECTION



The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.

PLASTIC BAG SUSPENSION



The plastic bag suspension on wheels allows an easy and convenient removal of the full shred bag.