

Head Office & Showroom:

Davy Avenue, Knowlhill
Milton Keynes MK5 8HJ
United Kingdom

Tel: +44 (0)1908 608888

Fax: +44 (0)1908 692399

www.morgana.co.uk

sales@morgana.co.uk



DigiBook 150

A new dimension to PUR Binding.
Four times stronger than hot melt.

PUR is the strongest, most flexible binding adhesive available and offers several additional advantages over other binding adhesives. When inks, coatings or digital print toners are present in the spine area these can compromise the strength of typical hotmelt perfect binding. PUR is resistant to this and will form a super-strong bond with all weights and finishes of paper stocks. In addition PUR works well with synthetic and recycled-content stock.

The DigiBook 150 is an entry level PUR binder and is ideally suited to traditional and digital printers who require short runs of PUR perfect bound books to a professional standard. The DigiBook 150 is equipped with a patented closed gluing system where the spine and side gluing is applied by a slot applicator for the utmost binding quality and accuracy.

Key product features:

- 150 Books per hour
- Touch screen operation
- Automatic opening and closing clamp
- Binding length (spine) from 110mm up to 380mm
- Spine thickness from 2 to 50 mm
- Spine preparation
- Paper chip extractor
- Patented hermetically sealed PUR application system for spine and side gluing with automatic glue cut-off
- Semi-automatic cleaning and sealing of the glue head

The machine is easy to use, even by non-specialised personnel, and operated via a touch screen panel with icon graphics.

An additional feature of the DigiBook 150 is the innovative glue application system. The application is direct and hermetically sealed, without odour or toxic fume emissions, and does not require extraction fans. It is possible to set different temperatures for the glue melting tank and the applicator giving greater flexibility and glue life. Another feature of this applicator is it can be cleaned and sealed automatically from the touch screen allowing for minimum glue wastage.

The PUR glue is applied on the book spine and on the sides by independent glue slots, each of which can be adjusted to give the best possible spine and side glue results.




DigiBook 150

A new dimension to PUR Binding.
Four times stronger than hot melt.



technical specifications



Books per hour	Up to 150
Number of clamps	1
Touch screen	Yes
Maximum book size	380mm x 320mm
Minimum book size	120mm x 110mm
Milling width	3mm
Block/spine thickness	2 - 50mm
Cover dimension maximum	700mm x 380mm
Cover dimension minimum	222mm x 120mm
Maximum cover weight	400 gsm
Dimensions	L 1400mm x W 800mm x H 1270mm
PUR glue tank capacity	Up to 3kg
Machine weight	400kg (gross) - 250kg (net)
Power requirement	220v, 13 amp

Note: the production speed varies according to material size

Compressed air required: minimum 7 bar/maximum 9 bar

***Disclaimer**

As part of our continued product improvement plan, specifications and information published here are subject to change without notice.

All specifications are dependent on application, type of stock, temperature, RH and print engine used.

Specifications quoted were measured on uncoated and unprinted stock.

E & OE.